

Xorcom CXW1000 – Swift - the all new member of the CompletePBX

Swift is an IP PBX featuring Xorcom's CompletePBX distribution, supporting VoIP extensions and trunks, Atribank telephony interfaces and IP gateways.

- * Static cooling
- * No moving parts
- * Complete silence



The Swift CXW1000 Small Business IP-PBX product line, based on CompletePBX, is compact, full-featured and budget-friendly.

The Swift CXW1000 is a stand-alone telephony solution featuring Xorcom's CompletePBX distribution and supporting various combinations of telephony ports. **30 Extensions CompletePBX license included** (upgradable to 500 Extensions)

Standard features

- SIP extensions, voicemail boxes, hunt groups, call center groups, and auto attendants (IVRs).
- Basic built-in call center with call recording, barge and whisper
- Emergency notification module
- Endpoint manager
- User-friendly Web interface
- Interface in different languages
- CDR (Call Details Record)
- TDM/SIP/IAX trunks
- Remote extensions
- Voicemail; Voicemail to email

Call capacity

- Concurrent calls: 30 (SIP only); 16 (PRI + FXS)
- Built in license: 30 Extensions (upgradable to 500 Extensions)



- Fax support; Fax to email
- IVR menu system
- Ring groups
- Call queues
- Conference rooms
- Find me / Follow me
- VmX Locator
- Time-based routing
- Advanced dialing rules
- Music-on-hold
- Paging and intercom
- Admin status screen

XORCOM CO.,LTD

Misgav Industrial Park, POB 60, D.N. Misgav 20174, Israel

Tel: +972-4-9951999; Fax: +972-4-9990287

Website: www.xorcom.com

Email: sales@xorcom.com

» SOFTWARE

Software version	Xorcom CompletePBX (ARM edition)
Linux version	Debian 11
GUI	Based on Ombutel
Security	Instruction protection software, firewall protection

» HARDWARE

Processor	Quad core Cortex-A72 (ARM v8) 64-bit SoC, 1.5GHz
RAM	2GB
Micro SD (flash memory)	32 GB or External storage
USB	2 x USB 2.0, 2 x USB 3.0
Video	2 x Micro HDMI

» POWER

Power Supply	5 VDC 3A
Voltage	Switching, auto adjust 100/240 Volts, 50/60 Hz
Power consumption	18 Watts (maximum)

» NETWORK

Ethernet port - standard	10/100/1000 Mb/s (x1)
---------------------------------	-----------------------

» ENVIRONMENT

Storage temperature	-20° to 70° Celsius (-4°-158° F)
Working temperature	0° to 40° Celsius (32°-104° F)
Humidity	20%-95%, non-condensing

» DIMENSION AND WEIGHT

Package Weight	0.445 kg (0.981 lbs)
Product Weight	0.225 kg (0.496 lbs)
Package Size	13.2 cm x 9.6 cm x 7.7 cm
Product Size	13 cm x 9 cm x 3 cm